


PROCEDURE OF REPLACEMENT




Switch off the engine and keep sparks, flames, cigarettes away from battery at all times, before removing the old battery.

1




Disconnect the negative terminal, first and avoid short-circuit caused by tools, when removing old battery.

2



Clean corroded parts in tray and cable clamps, before installation of new battery.

3



Connect the positive terminal, first and check the terminal clamps for tight fit, when installing new battery.

4

CAUTION



- No Sparks, Flames, or Smoking.
- Charge in well ventilated area.
- Remove from vehicle prior to charging.
- Read your vehicle, booster, and battery manuals prior to charging.
- In case of exposure to acid, flush immediately with water. Then get immediate medical help.
- Do not block or alter vent hole.
- Keep out of reach of children.

WARNING! LEAD ACID BATTERIES GENERATE EXPLOSIVE GASES. KEEP SPARKS, FLAMES, & LIGHTED CIGARETTES AWAY FROM BATTERY, WHEN CHARGING OR USING BATTERY IN AN ENCLOSED SPACE, PROVIDE VENTILATION. THIS BATTERY CONTAINS SULPHURIC ACID. AVOID CONTACT WITH SKIN, EYES, OR CLOTHING. IN EVENT OF ACCIDENT FLUSH WITH WATER AND CALL A PHYSICIAN IMMEDIATELY

MAXIMUM RECHARGING VOLTAGE IS 14.6V



BATTERY, WET, FILLED WITH ACID



Flammables



Read Instructions
Carefully



Keep out of
Reach of Children



Cautions of
Sulfuric Acid



Shield Eyes



Explosive